

SCHEDA TECNICA

FILTERING PRE SEPARATOR 450

IMPIANTI DI ASPIRAZIONE CENTRALIZZATI

The **filtering separator with a container**, with a diameter of **450 mm**, allows it to be connected to a **suction unit and to filter solid and liquid materials** with extreme simplicity and total safety. The **separator** is equipped with a **large surface pocket filter (90.000 cm²)**. The **filtering system** can be implemented with an **aluminized polyester cartridge system** with a large filtering surface, certified **M class** (filtration efficiency 1 micron). With the cartridge system, the **alternating air counter-current cleaning** of the filters is provided, which allows you to **clean the filters in a very effective way** without the need to stop the suction. There is also a **quick-release container on 65 Lt wheels** that allows you to **dispose of the vacuumed material** with extreme comfort.



DATI TECNICI

FILTRO PRIMARIO

Tipologia
Classe EN 60335-2-69

star filter
M Class

MACCHINA

Bocca aspirante 450Ø mm
Altezza 1.514mm

OPZIONI

⇨ **SISTEMI DI PULIZIA FILTRO DISPONIBILI**



SP

Pulizia cartucce in controcorrente d'aria
Filtro antistatico classe M (EN 60335-2-69)
3 Cartucce poliestere antistatico
9 m² superficie filtrante