

SCHEDA TECNICA

HF 10 Z22 I13D CENTRALIZED VACUUM

ASPIRATORI INDUSTRIALI ATEX ED ACD

The HF 10 ATEX Z22 industrial vacuum cleaner is a model designed to have maximum performance on fixed applications such as centralized systems, even large ones. The suction unit is mounted on a sturdy powder-coated steel frame. The very powerful ATEX-certified turbine is installed in the rear part of the aspirator protected by a sheet metal cover which also reduces the noise level. The front cylindrical chamber houses a large surface filtering system with an automatic filter cleaning system. Specifically, there are 4 independent cartridges in category M antistatic polyester, capable of retaining dust up to 1 micron in particle size. A totally automatic system allows keeping the filters always clean thanks to a jet of compressed air at 6 bar which, entering the cartridge, causes the dust to detach and fall towards the collection cone. Depending on the operational needs, it is possible to install different automatic and pneumatic unloading systems to maximize productivity and facilitate unloading into Big-bags.



POTENZA
7,5 kW



SUPERFICIE
120.000 cm²

DATI TECNICI

MOTORE

Marcatura ATEX	II 3 D Ex htc IIB T140°C Dc
Voltaggio	400V
Massimo vuoto	310mBar
Vuoto in continuo	270mBar
Massima portata d'aria	750m ³ /h
Livello di rumorosità	74dB(A)
Frequenza	50/60Hz
Potenza	10HP

FILTRO PRIMARIO

Tipologia	cartridge
Media	antistatic polyester
Efficienza filtrante (IFA)	IFA/BGIA M-PES EXAM ACCREDITED

OPZIONI



MEDIA FILTRANTE DISPONIBILE



HEPA 14

Filtro assoluto (EN 1822-5)

OPZIONI



SISTEMI DI PULIZIA FILTRO DISPONIBILI



SP

Pulizia cartucce in controcorrente d'aria
Filtro antistatico classe M (EN 60335-2-69)
4 Filtri poliestere antistatici
18 m² superficie filtrante

ACCESSORI



P12397

DOPPIO SCARICO FARFALLE ELETTROPNEUMATICHE Ø250MM ATEX

Sistema di scarico automatico con doppia farfalla elettropneumatica in diametro 250 mm certificato ATEX II3D Z22. Permette di scaricare il materiale dal cono di una tramoggia senza dover fermare l'aspirazione.



P12397

DOPPIO SCARICO FARFALLE ELETTROPNEUMATICHE Ø250MM ATEX

Sistema di scarico automatico con doppia farfalla elettropneumatica in diametro 250 mm certificato ATEX II3D Z22. Permette di scaricare il materiale dal cono di una tramoggia senza dover fermare l'aspirazione.