

SCHEDA TECNICA

MINIBULL BAGLESS INDUSTRIAL VACUUM

ASPIRATORI INDUSTRIALI WET&DRY MONOFASE

The Minibull is a **powerful** and **versatile** **bagless** industrial vacuum, useful for different professional applications. This vacuum cleaner is equipped with **two By-Pass motors** that work in parallel and ensure maximum **suction performance**. The filter is in sturdy polyester **M Class** (1μ filtration efficiency) to stop even **fine dust**. A different filter can be installed on this model depending on the application. **Teflon water-repellent filters**, **Nomex** 250°C resistant filters, and filters with **PTFE** treatment for more binding and **difficult dust** are also available. This **industrial vacuum** is equipped with a large 45 Lt detachable **container** that allows the operator to empty the vacuumed material easily. Disposable collection bags can also be used. A floating system can be provided in the container to **vacuum liquids** in complete **safety**.



POTENZA
2,6 kW



SUPERFICIE
15.000 cm²



CAPACITÀ
45 Lt

HIGHLIGHTS

SUCTION UNIT



The vacuum is generated by 2 by-pass motors. Each motor is managed by an independent switch, permitting the operator to control the intake performance. The motors are located in a sturdy casing, with an insulating sponge to maintain a low noise level.



MANUAL FILTER SHAKER

On one side of the filter chamber there is an ergonomic manual shaker through which the operator can easily and quickly clean the filter, removing any dust and debris from its surface. Thanks to this smart cleaning system the operator can carry on working without needing to change or wash the filter.



FILTERING ELEMENT

The filtration is guaranteed by an M class polyester filter. The star shape enables air to flow through the filter even when it is dirty. The fabric of the filter is classified as M Class (BIA | EN 60335-2-69). This means that all particles till 1 micron are stopped by the filter so as to protect the motors and the operator around the vacuum cleaner.



COLLECTION BIN

The material is collected inside a painted container equipped with a metal handle which enables the bin to be detached from the machine. Thanks to its 4 swiveling wheels, the bin can be easily moved and emptied.

DATI TECNICI

MOTORE

Tipologia	by-pass
Voltaggio	230V
Massimo vuoto	250mBar
Massima portata d'aria	380m3/h
Livello di rumorosità	72dB(A)
Motori	2
Frequenza	50/60Hz
Potenza	3,5HP

FILTO PRIMARIO

Tipologia	star filter
Classe EN 60335-2-69	M Class
Media	polyester
Pulizia filtro	manual shaker

MACCHINA

Bocca aspirante	70Ø mm
Dimensioni	550 x 620mm
Altezza	1.240mm
Peso	45Kg

OPZIONI



MEDIA FILTRANTE DISPONIBILE


ANT M
Filtro antistatico (Classe M EN 60335-2-69)

MTF
Filtro teflonato (Classe M EN 60335-2-69)

NOMEX
Filtro resistente 250° Celsius

PTFE
Filtro PTFE (Classe M EN 60335-2-69)

PTFE ANT
Filtro PTFE antistatico (Classe M EN 60335-2-69)

HEPA 14
Filtro assoluto (EN 1822)
22.000 cm² superficie filtrante
Classe H14 (EN 1822)
Fibra di vetro

OPZIONI

ALTRE OPZIONI


AB
Cassetta porta accessori

BX
Contenitore in acciaio INOX AISI 304

GX
Camera e contenitore acciaio INOX AISI 304

FLT
Dispositivo galleggiante per liquidi

GRD
Messa a terra

KDP
KIT differenziale di pressione per insaccamento

RC
Controllo remoto 24 V ON/OFF

RUOTE
Ruote antiraccia pivotanti

COSTRUZIONE IN ACCIAIO
Robusta costruzione in acciaio verniciato industriale

ACCESSORI


P11792
SPAZZOLA FISSA WET & DRY Ø 40MM
Accessorio fisso wet & dry con connessione a tubo flessibile D50 mm

P11792
SPAZZOLA FISSA WET & DRY Ø 40MM
Accessorio fisso wet & dry con connessione a tubo flessibile D50 mm

P11792
SPAZZOLA FISSA WET & DRY Ø 40MM
Accessorio fisso wet & dry con connessione a tubo flessibile D50 mm

P11792
SPAZZOLA FISSA WET & DRY Ø 40MM
Accessorio fisso wet & dry con connessione a tubo flessibile D50 mm