

SCHEDA TECNICA

RAM OIL 280 MP INDUSTRIAL VACUUM

ASPIRATORI INDUSTRIALI PER OLIO E TRUCIOLO

The **RAM OIL 280 MP** sump vacuum (capacity: 280 liters) finds wide use in **cleaning machining center tanks**, thanks to its speed in cleaning lubricating oils and metal chips. Suction is generated by **3 single-phase motors** operated by a single switch, which starts them sequentially, avoiding current peaks. There is a quick-release metal basket in the tank to separate the solid and liquid parts, and a **150-micron filter** that provides more effective filtration on metal parts. The electric float switch inserted inside the container stops the air flow when the maximum capacity is reached. With an **externally installed pump**, the container can be **fully emptied rapidly, without leaving any residue**. Since the pump is installed outside, the **whole container capacity can be used**. The vacuum cleaner comes standard with the oil and chip accessory kit and is equipped with a convenient accessory basket and two hose holder hooks.



POTENZA
3,9 kW



CAPACITÀ
280 Lt

HIGHLIGHTS
SUCTION UNIT


The vacuum is generated by 3 by-pass motors. Each motor is managed by an independent switch, permitting the operator to control the intake performance. The motors are located in a sturdy casing, with an insulating sponge to maintain a low noise level.


ROTATING INLET

Added to make any movements easier; Move around freely without twisting the industrial vacuum.


DISCHARGE SYSTEM

To empty the tank, the vacuum is equipped with an externally installed pump, which allows the full capacity of the container to be exploited and ensures complete emptying of the container, leaving no residue.


FILTERING ELEMENT

The collected liquid goes through a PPL filter with a 150 μ efficiency. Thanks to it's possible to separate even the smallest solid particles, making the filtered liquid suitable for reuse. The filter can be washed and reused easily. An disposable TNT filter (efficiency 100 μ).


ACCESSORY BASKET

A convenient storage solution for an easy access to all your accessories.


TWO HOSE HOLDER HOOKS

For a greater and improved convenience.

DATI TECNICI
MOTORE

Tipologia	by-pass
Voltaggio	230 110ableV
Massimo vuoto	250mBar
Massima portata d'aria	570m3/h
Livello di rumorosità	72dB(A)
Motori	3
Frequenza	50/60Hz
Potenza	5,2HP

MACCHINA

Bocca aspirante	50 \varnothing mm
Dimensioni	700 x 1.450mm
Altezza	1.400mm
Peso	220Kg
Capacità liquidi	280
Capacità solidi	40
Tempo di scarico	280/60

OPZIONI

ALTRE OPZIONI



BX

Contentitore in acciaio INOX AISI 304