

SCHEDA TECNICA

HF 18 CENTRALIZED VACUUM

IMPIANTI DI ASPIRAZIONE CENTRALIZZATI

The **HF 18 industrial vacuum** is designed for **maximum performance** on **fixed applications** such as large **centralized systems**. The machine is mounted on a **sturdy powder-coated steel frame**. The **Depureco HF 18 vacuum cleaner** is equipped with an extremely **powerful turbine** installed in the back of the **vacuum** and is protected by a sheet metal cover which also **reduces the noise level**. The front cylindrical chamber houses a large surface **filtering system** with an **automatic filter cleaning system**. Namely, there are **4 M Class independent anti-static polyester cartridges**, capable of retaining dust with a particle size of up to 1 micron. A fully **automatic system** that always keeps the **filters clean** thanks to a **6 bar compressed air blast**, which enters the cartridge causing the dust to detach and fall into the collection cone. A specific **discharge system**, to run continuously or not, can be installed according to operating n



POTENZA
12,5 kW



SUPERFICIE
45.000 cm²

DATI TECNICI

MOTORE

Voltaggio	400V
Massimo vuoto	420mBar
Vuoto in continuo	290mBar
Massima portata d'aria	1.120m ³ /h
Livello di rumorosità	74dB(A)
Frequenza	50/60Hz
Potenza	18HP

FILTRO PRIMARIO

Tipologia	star filter
Classe EN 60335-2-69	M Class
Media	polyester

OPZIONI



MEDIA FILTRANTE DISPONIBILE



HEPA 14

Filtro assoluto (EN 1822)
110.000 cm² superficie filtrante
Classe H14 (EN 1822)
Fibra di vetro

OPZIONI



SISTEMI DI PULIZIA FILTRO DISPONIBILI



SP

Pulizia cartucce in controcorrente d'aria
Filtro antistatico classe M (EN 60335-2-69)
4 Filtri poliestere antistatici
12 m² superficie filtrante

ACCESSORI



P12394

DOPPIO SCARICO FARFALLE ELETTROPNEUMATICHE Ø 150MM

Sistema di scarico automatico con doppia farfalla elettropneumatica in diametro 150 mm. Permette di scaricare il materiale dal cono di una tramoggia senza dover fermare l'aspirazione.



P12394

DOPPIO SCARICO FARFALLE ELETTROPNEUMATICHE Ø 150MM

Sistema di scarico automatico con doppia farfalla elettropneumatica in diametro 150 mm. Permette di scaricare il materiale dal cono di una tramoggia senza dover fermare l'aspirazione.



P12394

DOPPIO SCARICO FARFALLE ELETTROPNEUMATICHE Ø 150MM

Sistema di scarico automatico con doppia farfalla elettropneumatica in diametro 150 mm. Permette di scaricare il materiale dal cono di una tramoggia senza dover fermare l'aspirazione.