

SCHEDA TECNICA

PUMA 30 P ATEX Z20/Z22 I11/3D INDUSTRIAL VACUUM

ASPIRATORI INDUSTRIALI ATEX ED ACD

The Puma 30 P ATEX Z20/Z22 is an industrial vacuum cleaner of the heavy series, for working in harsh conditions and with heavy materials. The extractor has a third-party certification (TUV) which certifies the internal area as Z20. It mounts a dual-stage side channel blower in parallel/series with high airflow/depression. The safety vacuum breaker valve is installed as standard. The tangential inlet together with the robust cyclone welded inside the filtration chamber guarantees excellent efficiency even with the finest powders. The material, entering tangentially, meets the cyclone and due to the friction generated, it loses speed falling directly into the container. This system is very useful for protecting the filter from the sucked material. The filter is in polyester, M class certified, with a filtration efficiency of 1 μ . The filter can be customized according to the specific application. The industrial vacuum is equipped, as standard, with an automatic filter cleaning system which, thanks to an SP system in counter-current air, is able to keep the filter always clean easily and effectively, without having to interrupt the aspiration. A practical and sturdy 175 Lt container, equipped with a release system, allows you to collect the vacuumed material and dispose of it with ease. To facilitate the handling of the container there are 4 pivoting wheels mounted on reinforced supports in order to facilitate handling even when there are several kg of material inside. On request, a kit is available that allows the handling and unloading of the container with the forklift.



POTENZA
22 kW



SUPERFICIE
180.000 cm²



CAPACITÀ
175 Lt

HIGHLIGHTS

SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The side channel blower is equipped with a safety valve to guarantee continued work in complete safety, without any maintenance. The blower is also equipped with a metal silencer to maintain a low noise level.


FILTERING ELEMENT

The filtration is guaranteed by an M class polyester filter. The star shape enables air to flow through the filter even when it is dirty. The fabric of the filter is classified as M Class (BIA | EN 60335-2-69). This means that all particles till 1 micron are stopped by the filter so as to protect the blower and the operator around the vacuum cleaner.


SUCTION INLET

The tangential inlet is designed to ease the process of pushing the material down the bin. A sturdy metal cyclone welded inside the chamber slows the material's entry speed considerably down so that it falls directly inside the bin. This way, the filter is efficiently protected, minimizing clogging risk.


COLLECTION BIN

The vacuumed material is collected in an AISI 304 stainless steel container, equipped with a metal handle that enables the bin to be detached from the machine, to avoid any spark that could be generated by the electrostatic charge. Thanks to the 4 sturdy pivoting wheels, the bin can be moved very easily to then dispose of the collected material. Each wheel is reinforced to guarantee maximum stability during handling.

DATI TECNICI
MOTORE

Tipologia	side channel blower
Marcatura ATEX	II 1/3 D Ex htc IIIC T140°C Da/Dc
Voltaggio	400V
IP	65
Massimo vuoto	240mBar
Vuoto in continuo	200mBar
Massima portata d'aria	1.985m3/h
Valvola di sicurezza	included
Livello di rumorosità	78dB(A)
Frequenza	50/60Hz
Potenza	30HP
Classe di isolamento	F

FILTRO PRIMARIO

Tipologia	cartridge
Classe EN 60335-2-69	M Class
Media	antistatic polyester
Pulizia filtro	reverse jet
Efficienza filtrante (IFA)	IFA/BGIA M-PES EXAM ACCREDITED

MACCHINA

Bocca aspirante	130Ø mm
Dimensioni	1.050 x1.950mm
Altezza	2.300mm
Peso	560Kg
Ciclone conico	incluso

OPZIONI



MEDIA FILTRANTE DISPONIBILE



HEPA 14

Filtro assoluto (EN 1822)
110.000 cm² superficie filtrante
Classe H14 (EN 1822)
Fibra di vetro

OPZIONI

ALTRE OPZIONI



BX
Contenitore in acciaio INOX AISI 304



GX
Camera e contenitore acciaio INOX AISI 304



FKL
Supporto sollevamento per muletto



GFR
Golfari



RC
Controllo remoto 24 V ON/OFF

ACCESSORI



P12300/100
FLANGIA CONNESSIONE FLESSIBILE Ø 100MM
Flangia di accoppiamento su aspiratore industriale DF per tubo flessibile diametro 100 mm



P12300/100
FLANGIA CONNESSIONE FLESSIBILE Ø 100MM
Flangia di accoppiamento su aspiratore industriale DF per tubo flessibile diametro 100 mm



P12300/100
FLANGIA CONNESSIONE FLESSIBILE Ø 100MM
Flangia di accoppiamento su aspiratore industriale DF per tubo flessibile diametro 100 mm