

SCHEDA TECNICA

DF 075 Z2-Z22 I13GD INDUSTRIAL VACUUM

ASPIRATORI INDUSTRIALI ATEX ED ACD

The DF 075 Z2-Z22 is an ATEX Z22 certified industrial vacuum cleaner with a three-phase fan that allows you to vacuum volatile or suspended dust with an articulated arm or extraction hood. Inside the vacuum cleaner there is a large surface filter in antistatic polyester (24,000 cm²), M class certified, with a filtration efficiency of 1 micron, to vacuum electrostatically charged dust in total safety. In addition, it is possible to install an H14 filter for situations that require the suction of the finest dust. To clean the filter there is a very effective manual filter cleaning system as standard. Thanks to a lever outside the filtering chamber, the operator is able to shake the filter and deposit the dust directly in the collection container. On request, it is possible to install an automatic piston filter shaking system or a counter-current filter cleaning system. The unit is equipped with a release container on wheels with a capacity of 65Lt in AISI 304 stainless steel.




POTENZA
0,75 kW



SUPERFICIE
24.000 cm²



CAPACITÀ
65/100 Lt

HIGHLIGHTS

SUCTION UNIT

The vacuum is generated by an ATEX certified electric fan designed specifically to guarantee the best air flow while maintaining a good level of depression.


INLET DEFLECTOR

The inlet deflector is specifically designed to convey the material towards the container. Connection flanges or reduction flanges of different diameters (100 - 200 mm) can be attached to the deflector according to requirements.


FILTERING ELEMENT

The filtration is guaranteed by an M class polyester filter. The star shape enables air to flow through the filter even when it is dirty. The fabric of the filter is classified as M Class (BIA | EN 60335-2-69). This means that all particles till 1 micron are stopped by the filter so as to protect the blower and the operator around the vacuum cleaner.


COLLECTION BIN

The vacuumed material is collected in an AISI 304 stainless steel container, equipped with a metal handle that enables the bin to be detached from the machine, to avoid any spark that could be generated by the electrostatic charge. Thanks to the 4 sturdy pivoting wheels, the bin can be moved very easily to then dispose of the collected material. Each wheel is reinforced to guarantee maximum stability during handling.

DATI TECNICI
MOTORE

Tipologia	fan
Marcatura ATEX	II 3 G/D Ex htc IIIB T140°C Gc/Dc
Voltaggio	400V
IP	55
Massima portata d'aria	300 600800m ³ /h
Livello di rumorosità	65dB(A)
Frequenza	50/60Hz
Potenza	1HP
Classe di isolamento	F
Massimo vuoto	185 200180mm/H ₂ O
Depressione statica disponibile	180 192170

FILTRO PRIMARIO

Tipologia	star filter
Classe EN 60335-2-69	M Class
Media	antistatic polyester
Pulizia filtro	manual shaker

MACCHINA

Bocca aspirante	70 1000120Ø mm
Dimensioni	660 x 800mm
Altezza	1.630mm
Peso	80Kg
Ciclone conico	incluso

OPZIONI



MEDIA FILTRANTE DISPONIBILE



PTFE ANT

Filtro PTFE antistatico (Classe M EN 60335-2-69)

OPZIONI



SISTEMI DI PULIZIA FILTRO DISPONIBILI



PSC

Scuotifiltro Pneumatico



SP

Pulizia cartucce in controcorrente d'aria
Filtro antistatico classe M (EN 60335-2-69)
3 Cartucce poliestere antistatico
9 m² superficie filtrante

OPZIONI

ALTRE OPZIONI



100 LT

Contenitore 100 lt.



BX

Contenitore in acciaio INOX AISI 304



GX

Camera e contenitore acciaio INOX AISI 304

ACCESSORI



P10095

FASCETTA METALLICA Ø 100MM

Fascetta metallica a stringere con vite in acciaio zincato in diametro 100 mm



P10095

FASCETTA METALLICA Ø 100MM

Fascetta metallica a stringere con vite in acciaio zincato in diametro 100 mm



P10095

FASCETTA METALLICA Ø 100MM

Fascetta metallica a stringere con vite in acciaio zincato in diametro 100 mm



P10095

FASCETTA METALLICA Ø 100MM

Fascetta metallica a stringere con vite in acciaio zincato in diametro 100 mm



P12300/120

FLANGIA CONNESSIONE FLESSIBILE Ø 120MM

Flangia di accoppiamento su aspiratore industriale DF per tubo flessibile diametro 120 mm



P12300/120

FLANGIA CONNESSIONE FLESSIBILE Ø 120MM

Flangia di accoppiamento su aspiratore industriale DF per tubo flessibile diametro 120 mm



P12300/120

FLANGIA CONNESSIONE FLESSIBILE Ø 120MM

Flangia di accoppiamento su aspiratore industriale DF per tubo flessibile diametro 120 mm



P12300/120

FLANGIA CONNESSIONE FLESSIBILE Ø 120MM

Flangia di accoppiamento su aspiratore industriale DF per tubo flessibile diametro 120 mm



P12335/100

RIDUZIONE "Y" PER DF Ø 100/100MM

Biforcazione Y a due vie D100mm per aspiratori industriali DF



P12335/100

RIDUZIONE "Y" PER DF Ø 100/100MM

Biforcazione Y a due vie D100mm per aspiratori industriali DF



P12335/100

RIDUZIONE "Y" PER DF Ø 100/100MM

Biforcazione Y a due vie D100mm per aspiratori industriali DF