

## SCHEDA TECNICA

# M70 OIL INDUSTRIAL VACUUM CLEANER

## ASPIRATORI INDUSTRIALI PER OLIO E TRUCIOLO

The M70 OIL industrial vacuum cleaner is designed to suck up and separate oil and metal chips from tanks, on machine tool tables and guides. Suction is generated by two motors working in parallel, ensuring excellent suction speed. The container of this vacuum cleaner is equipped with a metal basket to separate the solid part from the liquid part and a 150-micron nylon filter for more effective filtration. The electric floating level switch automatically stops suction when the maximum capacity of the container is reached (70 lt of emulsified oil sucked in). Discharge is by gravity, thanks to a discharge tube located at the bottom of the container. Optionally, a discharge pump can be installed simultaneously with the suction of the filtered liquid. The M70 OIL industrial vacuum cleaner is mounted on wheels, the container allows the operator to easily empty the sucked material, so the liquid can also be discharged inside a collection or settling container.



**POTENZA**  
2,6 kW



**CAPACITÀ**  
70 Lt

**HIGHLIGHTS**
**VACUUM UNIT**


Suction is provided by 2 by-pass motors. Each motor is operated by an independent switch that allows the operator to control suction performance. The suction motors are located in a sturdy metal casing, with an insulating sponge to maintain a low noise level.

**FILTER UNIT**


The collected liquid passes through a PPL filter with an efficiency of 150 $\mu$ . Thanks to this, even the smallest solid particles can be separated, making the filtered liquid suitable for reuse. The filter can be washed and reused easily. A disposable TNT filter (100 $\mu$  efficiency) is also available.

**DISCHARGE SYSTEM**


To drain the collected liquid, the container is equipped with a drain tube at the bottom. The liquids are drained by gravity.

**DATI TECNICI**
**MOTORE**

Tipologia	by-pass
Voltaggio	230V
Massimo vuoto	250mBar
Massima portata d'aria	380m <sup>3</sup> /h
Livello di rumorosità	72dB(A)
Motori	2
Frequenza	50/60Hz
Potenza	3,5HP
Tempo di aspirazione	70/18

**MACCHINA**

Dimensioni	565 x 770mm
Altezza	1.415mm
Peso	48Kg
Capacità liquidi	70
Capacità solidi	40
Filtro olio	included
Tipologia di scarico	By gravity

**OPZIONI**

**ALTRE OPZIONI**



**TX**  
Contenitore camera e struttura in acciaio INOX AISI 304



**PUMP**  
Pompa per scarico in continuo  
Pompa immersa per scarico in continuo

**ACCESSORI**



**P12355**  
**OLIO E TRUCIOLO KIT PRO Ø 50MM**  
Kit completo di accessori specifici per applicazione aspirazione olio e trucioli in diametro 50 mm



**P12355**  
**OLIO E TRUCIOLO KIT PRO Ø 50MM**  
Kit completo di accessori specifici per applicazione aspirazione olio e trucioli in diametro 50 mm