

SCHEDA TECNICA

ATLAS 22 INDUSTRIAL VACUUM CLEANER FOR TRAILER INSTALLATION

Depureco's ATLAS industrial vacuum cleaner is the ideal solution for vacuuming and handling large amounts of material in industrial settings. Thanks to its powerful side channel turbine, it provides powerful, effective and constant suction even in continuous service and without the need for maintenance. The material is sucked inside a large hopper that can be lifted driven by a hydraulic system, making it easy to handle the sucked materials and to discharge them quickly and safely, thanks to the various discharge systems available. The vacuum cleaner also ensures optimal filtration, thanks to its system of 6 filter cartridges, which can be cleaned automatically with jets of compressed air without interrupting suction. The vacuum cleaner can be mounted on a trailer to be easily transported and positioned in any work place.



POTENZA
25 kW



SUPERFICIE
520.000 cm²



CAPACITÀ
756 Lt

HIGHLIGHTS

SIDE CHANNEL BLOWER

The suction unit is a side channel turbine with direct coupling between motor and impeller. The Side-Channel Turbine is equipped with a safety valve that ensures continuous work without any maintenance.


6X FILTER CARTRIDGES

The unit has a high-efficiency filtration system with 6 M-class cartridges and a filter surface area of 520000 cm². Depureco's SP system cleans the cartridges continuously with jets of compressed air, without stopping suction.


HYDRAULIC HOPPER

The ATLAS vacuum cleaner has a hydraulic hopper that can collect a large amount of heavy material. The hopper offers different discharge systems to suit every need.


TRANSPORT BY TRAILER

The ATLAS industrial vacuum cleaner can be transported anywhere by installing the unit on a trailer. *trailer not included.

DATI TECNICI
MOTORE

Tipologia	Side channel blower
Voltaggio	400V
IP	55
Vuoto in continuo	445mBar
Massima portata d'aria	1.100m ³ /h
Valvola di sicurezza	Included
Livello di rumorosità	74dB(A)
Frequenza	50/60Hz
Potenza	34HP
Classe di isolamento	F

FILTRO PRIMARIO

Tipologia	6x Cartridges
Classe EN 60335-2-69	IFA BGIAM-PES
Media	Polyester
Pulizia filtro	Automatic
Efficienza filtrante (IFA)	M class

MACCHINA

Bocca aspirante	100Ø mm
Dimensioni	3.746 X1.660mm
Altezza	2.063mm
Peso	1.300Kg
Altezza aperto	2.993
Diametro scarico	250

OPZIONI



MEDIA FILTRANTE DISPONIBILE



HEPA 14

Filtro assoluto (EN 1822)
110.000 cm² superficie filtrante
Classe H14 (EN 1822)
Fibra di vetro

OPZIONI

ALTRE OPZIONI



RC

Controllo remoto 24 V ON/OFF

ACCESSORI



P11887

KIT WET & DRY Ø 50MM

Kit completo di accessori specifici per aspirazione solidi e liquidi in diametro 50 mm