

SCHEDA TECNICA

TX 750 P JC LONGOPAC INDUSTRIAL VACUUM

The **TX 750 P JC Longopac** industrial vacuum cleaner stands out for its power, maneuverability, and compactness. Equipped with a **7.5 KW side channel blower**, it is ideal for maintenance-free continuous operation. Inside the filter chamber is a PTFE conical cartridge filter (35,000 cm²), certified **Class M (1 micron filtration efficiency)** ideal for working with even the most difficult dust. The unit can be equipped with an **H14 absolute filter** upon request. The **JetClean® filter cleaning system** allows the filter to be cleaned using the pressure differential between the inside and outside of the vacuum cleaner. Finally, the vacuum cleaner is equipped with a **Longopac collection system**, which automatically bags the sucked material into high-strength transparent plastic disposable bags, the volumes of which can be managed by the operator without coming into contact with the sucked material.



POTENZA
7,5 kW



SUPERFICIE
35.000 cm²



CAPACITÀ
Longopac

HIGHLIGHTS

VACUUM UNIT

The suction unit is a side channel turbine with direct coupling between motor and impeller. The turbine is equipped with a safety valve that ensures continuous, maintenance-free operation. A metal silencer is included as standard in the turbine to ensure a low noise level.


M-CLASS FILTER

Filtration is provided by a robust polyester cartridge filter. The cartridge is made to maintain a large filter surface area (35,000 cm²) in a compact space. This allows air to pass through even when the filter is dirty. The filter is class M certified (BIA | EN 60335-2-69) and stops particles down to 1 micron, preserving motors and the operator.


JET CLEAN FILTER CLEANING SYSTEM

The vacuum cleaner is equipped with a new filter cleaning system called JetClean® designed by Depureco. Due to the different pressure between the outside and the inside of the vacuum cleaner, the system generates a flow of air that passes through the cartridge and dislodges dust from the surface of the filter. It is a quick and efficient way to keep the filter clean while working, without stopping suction.


LONGOPAC®

The material is collected inside a durable plastic bag called Longopac® that is 20 metres long. The bag is rolled underneath the chamber and can be adapted to any requirement. Once the bag is filled, the operator can close it over the vacuumed material that automatically falls into it, seal it, cut off the segment of the bag with the debris and dispose of it safely, without any contact between operator and material.

DATI TECNICI
MOTORE

Tipologia	Side channel blower
Voltaggio	400V
Vuoto in continuo	260mBar
Massima portata d'aria	530m ³ /h
Valvola di sicurezza	included
Livello di rumorosità	79dB(A)
Frequenza	50/60Hz
Potenza	10HP

FILTRO PRIMARIO

Tipologia	Conical cartridge
Classe EN 60335-2-69	IFA BGIAM-PES
Media	PTFE
Pulizia filtro	Jet Clean
Efficienza filtrante (IFA)	M-class

MACCHINA

Bocca aspirante	70Ø mm
Dimensioni	650x1.100mm
Altezza	1.400mm
Peso	200Kg

OPZIONI



MEDIA FILTRANTE DISPONIBILE



HEPA 14

Filtro assoluto (EN 1822-5)

ACCESSORI



P10867

TERMINALE IN ACCIAIO Ø 70/40MM

Riduzione per innesto rapido aspiratore in acciaio zincato diametro 70/40 mm



P10867

TERMINALE IN ACCIAIO Ø 70/40MM

Riduzione per innesto rapido aspiratore in acciaio zincato diametro 70/40 mm



P10867

TERMINALE IN ACCIAIO Ø 70/40MM

Riduzione per innesto rapido aspiratore in acciaio zincato diametro 70/40 mm