

SINGLE-PHASE WET&DRY INDUSTRIAL VACUUM CLEANERS

WD 132 INDUSTRIAL VACUUM CLEANER FOR LIQUIDS





POTENZA 2,6 kW - 3,5 HP



APPLICAZIONE Liquids



CAPACITA' 130Lt




VANTAGGI

- 130 liters of liquid collection capacity
- High-strength steel construction

- Dual of interchangeable liquid/solid filtration system
- Manual valve for effortless discharge of sucked-in liquid

HIGHLIGHTS



SUCTION UNIT

Suction is provided by 2/3 by-pass motors operated by independent switches, allowing the operator to control suction performance. The motors are located inside a robust enclosure, with an insulating sponge to maintain a low noise level.



DUST/LIQUID FILTRATION KIT

Supplied with two washable filters, one polypropylene for liquid suction and one polyester for dust suction.



COLLECTION UNIT

The material is collected inside a large coated steel container that is easy to move thanks to the 4 sturdy wheels.



LIQUID DISCHARGE VALVE

A ball valve located at the bottom of the container allows the collected liquids to be easily discharged by gravity.

TECHNICAL DATA

| MUTURE | |
|------------------------|-----------------|
| Tipologie | By-pass |
| Potenza | 2,6 kW - 3,5 HP |
| Frequenza | 50/60 Hz |
| Voltaggio | 230 V |
| Vuoto in continuo | 250 mBar |
| Massima portata d'aria | 380 m3/h |
| Livello di rumorosità | 72 dB(A) |
| | |

| MACCHINA | |
|-------------------------------|-----------------|
| Bocca aspirante | 70 Ø mm |
| Sistema di raccolta | Steel container |
| Capacità | 130 Lt |
| Sistema di scarico liquidi | Discharge valve |
| Dimensioni | 580 x 530 mm |
| Altezza | 1160 mm |
| Peso | 38 Kg |

FILTRAZIONE

| Tipologia filtro primario | Bag |
|---------------------------|---------------------|
| Media | Polypropylene 1502m |
| Filtro aggiuntivo | Anti-foam filter |



DOTAZIONI



LIQUID LEVEL INDICATOR



DEFLECTORInternal deflector to protect the filter



PUSH HANDLE



VACUUM GAUGE

Vacuum gauge for indication of filter clogged or in need of replacement



POWER SUPPLY CABLE



SHUKO TYPE PLUG



WHEEL WITH BRAKE

Non-marking wheel with integrated brake



WHEELSNon-marking pivoting wheels



STEEL CONSTRUCTION

Rugged industrial coated steel construction



OPTIONS

STRUCTURE AND OPTIONS



60HZ

Available in 60Hz version



3 YEARS WARRANTY

Purchasing the replacement filter along with the vacuum



BX

Stainless steel bin AISI 304



GRDGrounding

ACCESSORIES



P11887

WET & DRY KIT Ø 50MM

Kit containing specific accessories for 50 mm diameter solids and liquids vacuuming



P13639

WET & DRY KIT Ø 40MM

Kit containing specific accessories for 40 mm diameter solids and liquids vacuuming