

DUST EXTRACTORS FOR TOXIC AND HAZARDOUS DUSTS

XFLOOR 3

INDUSTRIAL VACUUM CLEANER FOR SURFACE TREATMENT



POTENZA
3,9 kW - 5,2 HP



APPLICAZIONE
Toxic or hazardous dusts




TIPO DI RACCOLTA
Endless bag

VANTAGGI

- Industrial vacuum cleaner for fine dust
- Large surface area filter of class M
- Tangential inlet with cyclonic effect
- Endless Bag collection to avoid contact with dust

HIGHLIGHTS



SUCTION UNIT

Suction is provided by 3 by-pass motors controlled by a single switch that allows them to start sequentially, avoiding current spikes. The motors are inside a sturdy enclosure, with an insulating sponge to maintain a low noise level.



FILTER CLEANING SYSTEM

An ergonomic manual filter shaker allows the filter to be cleaned easily and quickly, removing dust and debris from the surface of the filter.



FILTER UNIT

The tangential inlet facilitates the cyclonic effect to deposit the collected material in the container. Filtration is ensured by a polyester star filter in class M (filtering efficiency 1 micron) with high filtering surface area, which guarantees air passage even with a dirty filter.



COLLECTION UNIT

The material is collected inside a sturdy 20-meter-long adjustable roll plastic bag. Once the bag is filled, simply seal and remove it, with no contact between operator and material.

TECHNICAL DATA

MOTORE

Tipologie	By-pass
Potenza	3,9 kW - 5,2 HP
Frequenza	50/60 Hz
Voltaggio	230 V
Vuoto in continuo	250 mBar
Massima portata d'aria	570 m3/h
Livello di rumorosità	72 dB(A)

MACCHINA

Bocca aspirante	80 Ø mm
Sistema di raccolta	Endless Bag
Dimensioni	920 x 565 mm
Altezza	1430 mm
Altezza compatto	1170 mm
Peso	70 Kg

FILTRAZIONE

Tipologia filtro primario	Star
Superficie filtrante	24000 cm2
Classe filtrazione EN 60335-2-69	M
Media	Polyester
Sistema Pulizia filtro	Manual

DOTAZIONI



PUSH HANDLE



VACUUM GAUGE

Vacuum gauge for indication of filter clogged or in need of replacement



POWER SUPPLY CABLE



SHUKO TYPE PLUG



WHEEL WITH BRAKE

Non-marking wheel with integrated brake



WHEELS

Non-marking pivoting wheels



STEEL CONSTRUCTION

Rugged industrial coated steel construction



LP

Endless Bag continuous roll collection system

OPTIONS

AVAILABLE FILTER MEDIA



PTFE ANT

Antistatic PTFE filter (M class EN 60335-2-69)




PTFE

PTFE Filter (M class EN 60335-2-69)



MTF

Teflon filter (M class EN 60335-2-69)



ANT M

Antistatic filter (M class EN 60335-2-69)

STRUCTURE AND OPTIONS

60^{Hz}

60HZ
Available in 60Hz version



3 YEARS WARRANTY
Purchasing the replacement filter along with the vacuum



TELESCOPIC CHASSIS
To reduce the footprint and facilitate transportation



RC SCHUKO
Remote control by power tool (MAX 2000 W)



GRD
Grounding

ACCESSORIES



P12350
STARTER KIT Ø 50MM
Basic kit containing specific accessories for 50 mm diameter solids and liquids vacuuming



P12348
DRY KIT Ø 50MM
Kit containing specific accessories for 50 mm diameter dust and solids vacuuming



P13640
DRY KIT Ø 40MM
Kit containing specific accessories for 40 mm diameter dust and solids vacuuming



P13638
STARTER KIT Ø 40MM
Basic kit containing specific accessories for 40 mm diameter solids and liquids vacuuming