

HEAVY DUTY THREE-PHASE INDUSTRIAL VACUUM CLEANERS

FOX 5,5 P

POWERFUL INDUSTRIAL VACUUM CLEANER



POTENZA
4 kW - 5,5 HP



APPLICAZIONE
Powders, solids and
shavings




CAPACITA'
100Lt

VANTAGGI


- Powerful and reliable industrial steel vacuum cleaner
- Suitable for continuous work, 24 hours a day, 7 days a week
- Cyclonic effect and high surface area M-class filter
- Multiple construction options available

HIGHLIGHTS



SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The turbine is equipped with a safety valve to ensure continuous, maintenance-free work. A metal silencer is included as standard in the turbine to ensure a low noise level.



FILTER UNIT

The tangential inlet facilitates the cyclonic effect to deposit the collected material in the container. Filtration is ensured by a polyester star filter in class M (filtering efficiency 1 micron) with high filtering surface area, which guarantees air passage even with a dirty filter.



FILTER CLEANING SYSTEM

An ergonomic manual filter shaker allows the filter to be cleaned easily and quickly, removing dust and debris from the filter surface.



COLLECTION UNIT

The material is collected inside a coated bin complete with a handle that allows it to be released. Thanks to the 4 sturdy pivoting wheels, the container can be moved with ease, and the collected material can then be disposed of.

TECHNICAL DATA

MOTORE

Tipologie	Side channel blower
Potenza	4 kW - 5,5 HP
Frequenza	50/60 Hz
Voltaggio	400 V
Vuoto in continuo	160 mBar
Massima portata d'aria	520 m3/h
Classe di isolamento	55 F IP
Livello di rumorosità	76 dB(A)

MACCHINA

Bocca aspirante	80 Ø mm
Sistema di raccolta	Steel container
Capacità	100 Lt
Dimensioni	660 X 1200 mm
Altezza	1510 mm
Peso	155 Kg
Valvola di sicurezza	Pressure relief valve

FILTRAZIONE

Tipologia filtro primario	Star
Superficie filtrante	24000 cm2
Classe filtrazione EN 60335-2-69	M
Media	Polyester
Sistema Pulizia filtro	Manual

DOTAZIONI



VACUUM GAUGE

Vacuum gauge for indication of filter clogged or in need of replacement



POWER SUPPLY CABLE



PLUG

4-pole industrial plug



WHEEL WITH BRAKE

Non-marking wheel with integrated brake



WHEELS

Non-marking pivoting wheels



STEEL CONSTRUCTION

Rugged industrial coated steel construction



CYCLONIC EFFECT

Tangential inlet and cyclone installed



PRV

Pressure relief valve installed

OPTIONS

AVAILABLE FILTER CLEANING SYSTEMS



SP

Automatic reverse jet cleaning system
Antistatic M class filter (EN 60335-2-69), 3
Polyester filter cartridges, 9 m² filter surface



PSC

Semiautomatic pneumatic filter shaker



SE

Semiautomatic electrical filter shaker



COM

Compressor on board
Compressor fitted on the back cover

AVAILABLE FILTER MEDIA



PTFE ANT

Antistatic PTFE filter (M class EN 60335-2-69)



PTFE

PTFE Filter (M class EN 60335-2-69)



NOMEX

250° Celsius resistant filter



MTF

Teflon filter (M class EN 60335-2-69)



BFL

M class filter 38.000 cm²



ANT M

Antistatic filter (M class EN 60335-2-69)



HEPA 14

Absolute filter (EN 1822)
22.000 cm² filter surface
H14 Class Filter (EN 1822)
Glass fiber

STRUCTURE AND OPTIONS

60^{Hz}

60HZ
Available in 60Hz version



3 YEARS WARRANTY
Purchasing the replacement filter along with the vacuum



THIRD PARTY ATEX CERTIFICATION



RC
Remote control 24V ON/OFF



KDP
Differential pressure KIT for bag



GRD
Grounding



GFR
Lifting eyebolts



FLT
Floater device



FKL
Forklift bracket



BX
Stainless steel bin AISI 304



GX
Stainless steel bin and chamber AISI 304



TX
Stainless steel bin, chamber and frame AISI 304



CONTAINER EMPTYING KIT
System for easy container emptying using forklift lifting.

ACCESSORIES



P13638
STARTER KIT Ø 40MM
 Basic kit containing specific accessories for 40 mm diameter solids and liquids vacuuming



P12350
STARTER KIT Ø 50MM
 Basic kit containing specific accessories for 50 mm diameter solids and liquids vacuuming



P13639
WET & DRY KIT Ø 40MM
 Kit containing specific accessories for 40 mm diameter solids and liquids vacuuming



P11887
WET & DRY KIT Ø 50MM
 Kit containing specific accessories for 50 mm diameter solids and liquids vacuuming



P12348
DRY KIT Ø 50MM
 Kit containing specific accessories for 50 mm diameter dust and solids vacuuming



P13640
DRY KIT Ø 40MM
 Kit containing specific accessories for 40 mm diameter dust and solids vacuuming



P01033
TILTING KIT FOR DUST BIN – BRACKET Ø 450MM
 Lifting bracket with forklift for 450 mm diameter container fitted with lifting ring. This way the vacuum's container can be lifted and tilt ...



P11287
TILTING KIT FOR DUST BIN – COMPLETE RING Ø 450MM
 Support ring for lifting a 450 mm diameter container. Essential if used with the lifting bracket. Thanks to these two devices, the container ...