

SUMP VACUUM CLEANERS FOR OIL AND CHIPS

M70 OIL INDUSTRIAL VACUUM CLEANER FOR OIL AND SWARF



Guarda il video!



POTENZA
2,6 kW - 3,5 HP



APPLICAZIONE
Oils and lubricants mixed
shavings

VANTAGGI

- Filters and reuses lubricating and cutting oils
- Simplified liquid collection and swarf management
- Simultaneous liquid suction and discharge possible
- Sturdy painted steel construction

HIGHLIGHTS




SUCTION UNIT

Suction is provided by 2 by-pass motors controlled by independent switches, allowing the operator to control suction performance. The motors are located inside a robust enclosure, with an insulating sponge to maintain a low noise level.



SEPARATION UNIT

The collected liquid passes through a grid basket, which traps the chips and simplifies their disposal. In this way, even the smallest solid particles can be separated, making the filtered liquid suitable for reuse.



SAFETY FLOATING DEVICE

An electric level probe immediately stops suction when the liquid exceeds a certain container fill level, protecting the suction unit.



LIQUID DISCHARGE VALVE

A ball valve located at the bottom of the container allows the collected liquids to be easily discharged by gravity.

TECHNICAL DATA

MOTORE

Tipologie	By-pass
Potenza	2,6 kW - 3,5 HP
Frequenza	50/60 Hz
Voltaggio	230 V
Vuoto in continuo	250 mBar
Massima portata d'aria	380 m3/h
Livello di rumorosità	70 dB(A)


MACCHINA

Bocca aspirante	50 Ø mm
Sistema di raccolta	Steel container
Capacità solido	40 lt
Capacità liquido	70 lt
Sistema di scarico liquidi	Discharge hose
Tempo di aspirazione	70/18 lt/sec
Dimensioni	565 x 770 mm
Altezza	1210 mm
Peso	48 Kg
Separazione solido	Basket grid

FILTRAZIONE

Filtro aggiuntivo	Anti-foam filter
-------------------	------------------

DOTAZIONI



DEFLECTOR
Internal deflector to protect the filter



OIL-PROOF CARTRIDGE
Oil-proof cartridge for motor protection



LIQUID DISCHARGE HOSE



ELECTRIC FLOATING DEVICE
System that automatically stops suction when the maximum level is reached



PUSH HANDLE



SHUKO TYPE PLUG



VACUUM GAUGE
Vacuum gauge for indication of filter clogged or in need of replacement



POWER SUPPLY CABLE



WHEEL WITH BRAKE
Non-marking wheel with integrated brake



WHEELS
Non-marking pivoting wheels



STEEL CONSTRUCTION
Rugged industrial coated steel construction

OPTIONS

STRUCTURE AND OPTIONS

60^{Hz}

60HZ
Available in 60Hz version



HOSE WITH DISCHARGE VALVE



PUMP
Continuous discharge pump

Submerged pump for
continuous discharge



BX
Stainless steel bin AISI 304



GX
Stainless steel bin and chamber AISI 304

ACCESSORIES



P12351
OIL & SWARF KIT Ø 40MM.
Basic kit containing specific accessories for 40 mm diameter oil and swarf vacuuming application



P12352
OIL & SWARF KIT Ø 50MM.
Basic kit containing specific accessories for 50 mm diameter oil and swarf vacuuming application



P12354
OIL & SWARF KIT PRO Ø 40MM
Kit containing specific accessories for 40 mm diameter oil and swarf vacuuming application



P12355
OIL & SWARF KIT PRO Ø 50MM
Kit containing specific accessories for 50 mm diameter oil and swarf vacuuming application