

HEAVY DUTY THREE-PHASE INDUSTRIAL VACUUM CLEANERS

TX 300 SP INDUSTRIAL WHEELED VACUUM CLEANER WITH AUTOMATIC FILTER CLEANING



Guarda il video!





3 kW - 4 HP



APPLICAZIONE
Fine, dry and clogging
powders




CAPACITA' 100Lt



VANTAGGI

- Industrial steel vacuum cleaner, powerful and reliable
- Suitable for continuous work, 24 hours a day, 7 days a week
- Suitable for extracting large quantities of fine and light dusts
- Multiple construction options available

HIGHLIGHTS



SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The turbine is equipped with a safety valve to ensure continuous, maintenance-free work. A metal silencer is included as standard in the turbine to ensure a low noise level.



FILTER UNIT

Filtration is ensured by polyester cartridge filters in class M (filtration efficiency 1 micron) with high filtering surface area, which guarantees the passage of air even with dirty filter.



SP FILTER CLEANING SYSTEM

Automatic filter cleaning system in reverse flow of air at 6 bar (compressed air not supplied as standard). Each filter is cleaned at regular, adjustable intervals alternately without interrupting suction. Ideal for fine and difficult dust.



COLLECTION UNIT

The material is collected inside a coated bin complete with a handle that allows it to be released. Thanks to the 4 sturdy pivoting wheels, the container can be moved with ease, and the collected material can then be disposed of.

TECHNICAL DATA

MOTORE	
Tipologie	Side channel blower
Potenza	3 kW - 4 HP
Frequenza	50/60 Hz
Voltaggio	400 V
Vuoto in continuo	230 mBar
Massima portata d'aria	350 m3/h
Classe di isolamento	55 F IP
Livello di rumorosità	74 dB(A)

MACCHINA

Bocca aspirante	70 Ø mm
Sistema di raccolta	Steel container
Capacità	100 Lt
Dimensioni	650 X 1100 mm
Altezza	1750 mm
Peso	130 Kg

FILTRAZIONE

Tipologia filtro primario	3x Cartridges
Superficie filtrante	90000 cm2
Classe filtrazione EN 60335-2-69	М
Media	Antistatic polyester
Sistema Pulizia filtro	Automatic SP



DOTAZIONI



VACUUM GAUGE

Vacuum gauge for indication of filter clogged or in need of replacement



POWER SUPPLY CABLE



DEFLECTOR

Internal deflector to protect the filter



WHEEL WITH BRAKE

Non-marking wheel with integrated brake



WHEELS

Non-marking pivoting wheels



STEEL CONSTRUCTION

Rugged industrial coated steel construction



100 LT

100 Lt bin



PLUG

4-pole industrial plug

OPTIONS

AVAILABLE FILTER CLEANING SYSTEMS



COM

Compressor on board Compressor fitted on the back cover



AVAILABLE FILTER MEDIA



HEPA 14 Absolute filter (EN 1822) 28.000 cm² filter surface H14 Class Filter (EN 1822) Glass fiber



STRUCTURE AND OPTIONS

60[®]_{HZ}

60HZ

Available in 60Hz version



3 YEARS WARRANTY

Purchasing the replacement filter along with



ATEX CERTIFICATION



CYCLONIC EFFECT

Tangential inlet and cyclone installed Tangential inlet + cyclone



RC

Remote control 24V ON/OFF



PRV

Pressure relief valve installed



LP

Endless Bag continuous roll collection system



KDP

Differential pressure KIT for bag



GRD

Grounding



GFR

Lifting eyebolts



FLT

Floater device



FKL

Forklift bracket



BX

Stainless steel bin AISI 304



GX

Stainless steel bin and chamber AISI 304



Stainless steel bin, chamber and frame AISI 304



CONTAINER EMPTYING KIT

System for easy container emptying using forklift lifting.



ACCESSORIES



P13970

ARTICULATED SUCTION ARM D70

Flexible PVC suction arm, retrofittable on existing models - 1.2 mt length - d70



P13638

STARTER KIT Ø 40MM

Basic kit containing specific accessories for 40 mm diameter solids and liquids vacuuming



P12350

STARTER KIT Ø 50MM

Basic kit containing specific accessories for 50 mm diameter solids and liquids vacuuming



P13639

WET & DRY KIT Ø 40MM

Kit containing specific accessories for 40 mm diameter solids and liquids vacuuming



P11887

WET & DRY KIT Ø 50MM

Kit containing specific accessories for 50 mm diameter solids and liquids vacuuming



P13640

DRY KIT Ø 40MM

Kit containing specific accessories for 40 mm diameter dust and solids vacuuming



P12348

DRY KIT Ø 50MM

Kit containing specific accessories for 50 mm diameter dust and solids vacuuming