

DUST COLLECTORS

DF 22

DUST COLLECTOR



Guarda il video!



POTENZA
2,2 kW - 3 HP



APPLICAZIONE
Volatile and suspended
powders



CAPACITA'
65Lt

VANTAGGI

- Very high air flow rates for suspended dust
- High filtration capacity and efficiency
- Sturdy painted steel construction
- Suction arm available (also Atex certified)

HIGHLIGHTS



SUCTION UNIT

The suction is generated by a specially designed electric fan to ensure the best air flow rate while maintaining a good level of water lift.




FILTER UNIT

The material is diverted by a deflector protecting the main filter. Filtration is ensured by a class M polyester star filter (filtration efficiency 1 micron) with high filtering surface area, which guarantees air passage even with the dirty filter.



FILTER CLEANING SYSTEM

An ergonomic manual filter shaker allows the filter to be cleaned easily and quickly, removing dust and debris from the surface of the filter.



COLLECTION UNIT

The material is collected inside a coated container complete with a handle that allows its release. Thanks to the 4 sturdy pivoting wheels, the container can be moved with ease, and the collected material can then be disposed of.

TECHNICAL DATA

MOTORE

Tipologie	Electric Fan
Potenza	2,2 kW - 3 HP
Frequenza	50/60 Hz
Voltaggio	400 V
Massimo vuoto mmH2O	350 350 350 mmH2O
Livello depressione statica	340 320 280 mmH2O
Massima portata d'aria	800 1000 1400 m3/h
Classe di isolamento	55 F IP
Livello di rumorosità	73 dB(A)

MACCHINA

Bocca aspirante	100 120 150 Ø mm
Sistema di raccolta	Steel container
Capacità	65 Lt
Dimensioni	660 x 800 mm
Altezza	1630 mm
Peso	120 Kg

FILTRAZIONE

Tipologia filtro primario	Star
Superficie filtrante	24000 cm2
Classe filtrazione EN 60335-2-69	M
Media	Polyester
Sistema Pulizia filtro	Manual

DOTAZIONI



PUSH HANDLE



PLUG
4-pole industrial plug



POWER SUPPLY CABLE



WHEEL WITH BRAKE
Non-marking wheel with integrated brake



WHEELS
Non-marking pivoting wheels



STEEL CONSTRUCTION
Rugged industrial coated steel construction

OPTIONS

AVAILABLE FILTER CLEANING SYSTEMS



SP
Automatic reverse jet cleaning system
Antistatic M class filter (EN 60335-2-69), 3
Polyester filter cartridges, 9 m² filter surface

AVAILABLE FILTER MEDIA



HEPA 13
Absolute filter (EN 1822)
35.000 cm² filter surface
H13 Class Filter (EN 1822)
Glass fiber



PTFE ANT
Antistatic PTFE filter (M class EN 60335-2-69)



PTFE
PTFE Filter (M class EN 60335-2-69)



NOMEX
250° Celsius resistant filter



BFL
M class filter 38.000 cm²



ANT M
Antistatic filter (M class EN 60335-2-69)



ACB
Active carbon filter

STRUCTURE AND OPTIONS

60^{Hz}

60HZ
Available in 60Hz version



3 YEARS WARRANTY
Purchasing the replacement filter along with the vacuum



GRD
Grounding



GX
Stainless steel bin and chamber AISI 304



BX
Stainless steel bin AISI 304



100 LT
100 Lt bin



SPARK TRAP
Built to capture sparks produced during welding, sanding, or polishing operations on metal parts

ACCESSORIES

P12336
SUCTION ARM Ø 160MM/L 3M

160mm diameter suction arm jointed in three parts for a total length of 3 metres, equipped with an articulated hood and valve for adjusting ...


P12300/200
FLANGED REDUCTION FOR HOSE Ø 200MM

Coupling flange on DF industrial vacuum for 200 mm diameter flexible hose


P12300/180
FLANGED REDUCTION FOR HOSE Ø 180MM

Coupling flange on DF industrial vacuum for 180 mm diameter flexible hose


P12300/150
FLANGED REDUCTION FOR HOSE Ø 150MM

Coupling flange on DF industrial vacuum for 150 mm diameter flexible hose


P12300/120
FLANGED REDUCTION FOR HOSE Ø 120MM

Coupling flange on DF industrial vacuum for 120 mm diameter flexible hose


P12300/100
FLANGED REDUCTION FOR HOSE Ø 100MM

Coupling flange on DF industrial vacuum for 100 mm diameter flexible hose


P12334
FLANGED REDUCTION FOR ARM Ø 160MM

Coupling flange on DF industrial vacuum for 160 mm diameter flanged arm