

WELDING FUME EXTRACTORS

XM TOOLS

INDUSTRIAL VACUUM FOR MECHANICAL PROCESSING



POTENZA
1,3 kW - 1,8 HP



APPLICAZIONE
Powders, solids and
shavings



CAPACITA'
20Lt

VANTAGGI

- Compact and easy to handle
- Multi-stage filtration for maximum operator safety
- Sturdy painted steel construction
- Possibility of direct remote control from power tool

HIGHLIGHTS




SUCTION UNIT

Suction is provided by 1 by-pass motor placed inside a robust casing, with an insulating sponge to maintain a low noise level.




FILTER UNIT

Filtration is ensured by a Class M polyester cartridge filter (filtration efficiency 1 micron) with a high filtering surface area, which guarantees air passage even with a dirty filter.



JET CLEAN FILTER CLEANING SYSTEM

Equipped with JetClean® filter cleaning system. Due to the different pressure between the outside and inside of the vacuum cleaner, the system generates a flow of air through the cartridge that detaches dust from the surface of the filter, keeping the filter efficient while working and without stopping suction.



REMOTE CONTROL

Passing the electric cable of the welding machine through the clip, the vacuum unit automatically begins suction when the operator starts welding and ends a few seconds after the welding machine is turned off.

TECHNICAL DATA

MOTORE

Tipologie	By-pass
Potenza	1,3 kW - 1,8 HP
Frequenza	50/60 Hz
Voltaggio	230 V
Vuoto in continuo	250 mBar
Massima portata d'aria	190 m3/h
Livello di rumorosità	72 dB(A)
Controllo Remoto	Power tool socket

MACCHINA

Bocca aspirante	50 Ø mm
Sistema di raccolta	Steel container
Capacità	20 Lt
Dimensioni	534 x 471 mm
Altezza	983 mm
Peso	36 Kg

FILTRAZIONE

Tipologia filtro primario	Cartridge
Superficie filtrante	35000 cm2
Classe filtrazione EN 60335-2-69	M
Media	PTFE coated polyester
Sistema Pulizia filtro	Jet Clean
Ghigliottina JetClean	Included

DOTAZIONI



SHUKO TYPE PLUG



FILTER CLOGGING INDICATOR

Filter clogged or need to be replaced
indicator light



POWER SUPPLY CABLE



WHEEL WITH BRAKE

Non-marking wheel with integrated brake



WHEELS

Non-marking pivoting wheels



STEEL CONSTRUCTION

Rugged industrial coated steel construction



JC

Jet Clean

OPTIONS

AVAILABLE FILTER MEDIA



HEPA 13

Absolute filter (EN 1822)
35.000 cm² filter surface
H13 Class Filter (EN 1822)
Glass fiber



HEPA 14

Absolute filter (EN 1822)
22.000 cm² filter surface
H14 Class Filter (EN 1822)
Glass fiber

STRUCTURE AND OPTIONS

60^{Hz}

60HZ
Available in 60Hz version



3 YEARS WARRANTY
Purchasing the replacement filter along with the vacuum



BX
Stainless steel bin AISI 304




GRD
Grounding

ACCESSORIES



P13638
STARTER KIT Ø 40MM
Basic kit containing specific accessories for 40 mm diameter solids and liquids vacuuming



P12000
SUCTION HOOD (400X50MM)
Galvanised steel suction hood for welding fumes or suspended dusts. Connection for 50mm diameter pipe with bracket and magnet for positionin ...