

VACUUM CLEANERS FOR SCRAP, PACKAGING AND OEM

AS 085 INDUSTRIAL VACUUM FOR TRIMS, PRODUCTION CUTTINGS AND WASTE






VANTAGGI

- Suction of trims and bulky cuttings
- Large collection capacity

- Can be installed directly on production lines
- Window to check fill level

HIGHLIGHTS



SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The turbine is equipped with a safety valve that ensures continuous, maintenance-free operation. A metal silencer is included as standard in the turbine to ensure a low noise level.



FILTERING COLLECTION BAG

Polyester bag filter for material collection that compacts material to the bottom, thus enabling the suction of large amounts of material



COLLECTION UNIT

The material is collected inside the large steel vacuum chamber, which is easy to move thanks to the 4 sturdy wheels.



LEVEL INSPECTION DOOR

An inspection window allows inspection of the amount of material inside the container without having to open the top cover

TECHNICAL DATA

MOTORE

Tipologie	Side channel blower
Potenza	0,85 kW - 1,2 HP
Frequenza	50/60 Hz
Voltaggio	400 V
Vuoto in continuo	160 mBar
Massima portata d'aria	150 m3/h
Classe di isolamento	55 F IP
Livello di rumorosità	64 dB(A)

MACCHINA

Bocca aspirante	50 Ø mm
Sistema di raccolta	Steel container
Capacità	120 Lt
Dimensioni	510 x 590 mm
Altezza	1440 mm
Peso	58 Kg
Valvola di sicurezza	Pressure relief valve

FILTRAZIONE

Tipologia filtro primario	Bag
Media	Polyester



DOTAZIONI



POWER SUPPLY CABLE



PLUG 4-pole industrial plug



WHEEL WITH BRAKE Non-marking wheel with integrated brake



WHEELS Non-marking pivoting wheels



STEEL CONSTRUCTION Rugged industrial coated steel construction



PRV Pressure relief valve installed

OPTIONS

STRUCTURE AND OPTIONS



60HZ Available in 60Hz version



3 YEARS WARRANTY Purchasing the replacement filter along with the vacuum



GRD Grounding



TX Stainless steel bin, chamber and frame AISI 304