

CENTRAL VACUUM SYSTEMS

# CVS 200 P

## SUCTION UNIT FOR CENTRALIZED SYSTEMS



**POTENZA**  
22 kW - 30 HP



**APPLICAZIONE**  
Powders, solids and  
shavings

## VANTAGGI

- Powerful side-channel blowers suitable for continuous operation
- Easy to move with a forklift truck
- Reliable suction unit for centralized suction systems
- Multiple construction options available

## HIGHLIGHTS



### SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The Side Channel Blower is equipped with a safety valve to ensure continuous, maintenance-free operation.



### EASY HANDLING

Two pass-through guides located on the bottom facilitate handling of the unit by forklift truck



### ELECTRICAL PANEL WITH REMOTE START

Management via electrical panel equipped with star/delta start and remote control. Implementable with additional functions



### REQUIRES FILTRATION UNIT

This unit does not include filtration and collection units, it requires coupling with a filter pre-separator or similar unit

## TECHNICAL DATA

### MOTORE

Tipologie	Side channel blower
Potenza	22 kW - 30 HP
Frequenza	50/60 Hz
Voltaggio	400 V
Vuoto in continuo	275 mBar
Massima portata d'aria	1770 m3/h
Classe di isolamento	55   F IP
Livello di rumorosità	78 dB(A)
Controllo Remoto	Free connector available
Quadro elettrico	Included

### MACCHINA

Bocca aspirante	127 Ø mm
Dimensioni	821 x 1319 mm
Altezza	1792 mm
Valvola di sicurezza	Pressure relief valve
Supporto sollevamento muletto	Included

## DOTAZIONI



### ELECTRICAL PANEL

Electrical panel, implementable with additional functions



### PLUG

4-pole industrial plug



### VACUUM GAUGE

Vacuum gauge for indication of filter clogged or in need of replacement



### POWER SUPPLY CABLE



### STEEL CONSTRUCTION

Rugged industrial coated steel construction



### PRV

Pressure relief valve installed

## OPTIONS

### AVAILABLE FILTER MEDIA



### HEPA 14

Absolute filter (EN 1822)  
110.000 cm<sup>2</sup> filter surface  
H14 Class Filter (EN 1822)  
Glass fiber

## STRUCTURE AND OPTIONS

**60<sup>✓</sup>Hz**

**60HZ**

Available in 60Hz version



**3 YEARS WARRANTY**

Purchasing the replacement filter along with the vacuum